



CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

DoP No: LAI.DC.007

1. Unique identification code of the product-type:

31 947 (Fig 6 Application)

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4) of the CPR:

31 947 Single Action Surface Mounted (Fig 6 Application)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use on fire and smoke compartmentation doors, when fitted in accordance with the manufacturer's fitting instructions.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5):

**LIDLAW LIMITED
STRAWBERRY LANE, WILLENHALL,
WEST MIDLANDS WV13 3RS,
UNITED KINGDOM**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard. Please give the Notified Body Number

EN1154: 1996: A1:2002 Notified Body No. 1121 issued the EC Certificate

8. European Technical Assessment:

N/A

9. Declared performance

Essential characteristic Self Closing	Performance	Harmonised technical Specification
5.2.1. General		EN 1154:1996:A1:2002
Application (o/hd door closer	Door Mount Push Side Fig 66/6	
5.2.2. Durability	500,000 test cycles	
5.2.3. Closing moment	Pass Size 5	
5.2.4. Opening moment	Pass Size 5	
5.2.5. Efficiency	More than 65% size 5	
5.2.6. Closing time	Pass	
5.2.7. Angles of operation	Grade 3, 150°C	
5.2.8. Overload performance	Pass	
5.2.9. Temperature dependence	-15°C to + 40°C	
5.2.10. Fluid leakage	Pass	
5.2.11. Damage	Pass	
5.1.12 Latch control	Pass	
5.1.13. Backcheck	N/A	
5.1.14 Delayed closing	N/A	
5.1.15. Adj closing force	N/A	
5.1.16. Zero position (double action only)	N/A	
5.1.18 Fire/smoke doors	Pass see other documents for details	
Essential characteristic Durability of Self closing	Performance	Harmonised technical specification
5.2.2. Durability	500,000 test cycles	
5.2.17.1 Corrosion	Grade 3	
5.2.17.2. Corrosion	Pass	
Dangerous Substances Annex ZA3	The materials in the products(s) do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacture identified in point 4.

Signed for and on behalf of the manufacturer by:

Mr Steve Lee
 Chief Executive Officer
 Date of issue: 01/03/2018
 Strawberry Lane
 Wolverhampton, West Midlands WV13 3RS
 United Kingdom

