



## CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

**DoP No. LAI.ML.010**

1. Unique identification code of the product-type:

**11 961/ 11 961R Cylinder Sashlock**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**11 961/ 11 961R Cylinder Sashlock**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**For use on fire and smoke compartmentation doors**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**LIDLAW LIMITED  
STRAWBERRY LANE, WILLENHALL,  
WEST MIDLANDS WV13 3RS,  
UNITED KINGDOM**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 1**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 12209: 2003 /AC 2005  
Notified testing laboratory No.1121 performed the type testing and issued test reports.**

8. European Technical Assessment:

**N/A**

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
<b>Self closing</b> 5.4.2 Closing force  5.1.2 Re-latching force of latch bolt	Grade 8, ≤ 200 Kg door mass, 15 N maximum closing force  >2.5N	EN 12209: 2003 /AC 2005
<b>Durability of self closing</b> 5.3.1 Durability of latch action	Grade X, ≤200,000 test cycles, 120N side load on latch bolt.	
<b>Ability to maintain the door in the closed position and not contribute to its spread of fire</b>	Grade 1	
<b>Control of Dangerous substances</b>	If a reference to dangerous substances is added in the table ZA.1, the following claim is suggested: Pass: the materials in the lock do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

Mr Steve Lee  
 Chief Executive Officer  
 Date of issue: 01/03/2018  
 Strawberry Lane  
 Wolverhampton, West Midlands WV13 3RS  
 United Kingdom

