

# CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

#### DoP No. LAI.PE.011

1. Unique identification code of the product-type:

### **Orbis 800 Series Panic Exit Devices (Surface Mounted)**

2 Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Orbis 59 841.1, 59 840.1, 59 842.1, 59 843.1, 59 841.2, 59 840.2, 59 842.2 and 59 843.2

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For use on; fire / smoke compartment doors and doors on escape routes, when fitted in accordance with the manufacturer's fitting instructions.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

#### LAIDLAW LIMITED STRAWBERRY LANE, WILLENHALL, WEST MIDLANDS WV13 3RS, UNITED KINGDOM

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

#### N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

#### System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Standard EN1125: 2008

Notified Certification body No.1121 performed the type testing and issued test reports.

8. European Technical Assessment:

N/A

## 9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Ability to release		•
(for doors on escape routes)		
4.1.2 Release function	Releases Immediately (<1s)	EN 1125:2008
4.1.3 Panic exit device mounting	Surface Mounted	_
4.1.5 Exposed edges and corners	Satisfactory	_
4.1.7 Double doorset	Pass	_
4.1.9 Bar installation	<150mm	_
4.1.10 Bar length	>60%	_
4.1.11 Bar projection	Category 2 (<100mm)	_
4.1.12 Bar end	N/A	_
4.1.13 Operating bar face	55mm	_
4.1.14 Test rod	Pass	_
4.1.15 Door face gap	>25mm	_
4.1.16 Accessible gap	Pass	_
4.1.17 Door free movement	Pass	_
4.1.18 Top vertical bolt	Pass (where applicable)	_
4.1.19 Keepers	Pass	4
4.1.21 Keepers dimensions	Pass	4
4.1.23 Door mass and dimensions	Variants in list 1:	
	2250mm X 900mm; 200kg	
	Variants in list 2:	
4.4.24 Outside seeses device	2250mm X 1200mm; 200kg	_
4.1.24 Outside access device 4.2.2 Release forces	Pass	4
4.2.7 Security requirement	≤ 80N and ≤ 220N under pressure Grade 2	_
Durability of ability to release against aging	Grade 2	-
degradation		
(for doors on escape routes)		
4.1.4; 4.2.9 Corrosion resistance	Grade 3 (96 Hours)	┥
4.1.6 Temperature range	Suitable for operation between:	-
4.1.0 Temperature range	-10°C and + 60°C	
4.1.19; 4.2.6 Covers for vertical rods	Pass	╡
4.1.22 Lubrication	Every 20,000 cycles	╡
4.2.3 Re-engagement force	Pass (≤50N)	7
4.2.4 Durability	200,000 cycles	╡
4.2.5 Abuse resistance –Horizontal bar	Pass	╡
4.2.6 Abuse resistance – Vertical rod	Pass	╡
4.2.8; 4.2.2; 4.1.17 Final examination	Pass	
Self closing ability C	1 400	
(for fire/smoke doors on escape routes)		
4.2.3 Re-engagement force	Pass (≤50N)	7
Durability of Self closing ability C against		╡
aging degradation		
(for fire/smoke doors on escape routes)		
4.2.4 Durability	200,000 cycles	7
4.2.3 Re-engagement force	Pass (≤50N)	7
Resistance to fire E (integrity) and I (insulation		7
(for fire doors on escape routes)		
4.1.8; Annex B - Suitability of panic exit devices for	r Grade B	
use on fire resisting doorsets assemblies -		
Additional requirements		_
Control of Dangerous substances		_
4.1.25 Control of Dangerous substances	Pass -The materials in the device do	
	not contain or release any dangerous	
	substances in excess of the maximum	
	levels specified in existing European	
	material standards of any national	
	regulations	1

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

## Signed for and on behalf of the manufacturer by:

Mr Steve Lee Chief Executive Officer Date of issue: 01/03/2018 Strawberry Lane Wolverhampton, West Midlands WV13 3RS United Kingdom